


**SERVICE NOTES:**

- 1. REFER TO TYPICAL POTABLE WATER SERVICE TOHO-01.0 FOR SERVICE NOTES.

**METER AND METER BOX PLACEMENT NOTES**

- 1. METERS 3/4" TO 1" ARE PAID FOR BY THE DEVELOPER AND INSTALLED BY TOHO.
- 2. METER BOX(ES), SERVICE LINE(S), AND ALL ASSOCIATED APPURTENANCES ARE THE RESPONSIBILITY OF THE CONTRACTOR AND/OR DEVELOPER.
- 3. APPROVED BACKFLOW DEVICES ARE REQUIRED ON ALL IRRIGATION SERVICES COVERED BY THIS DETAIL AND ARE THE RESPONSIBILITY OF THE CONTRACTOR AND/OR DEVELOPER:
  - 3.1. RPZ BACKFLOW DEVICES SHALL BE INSTALLED A MINIMUM OF 12" ABOVE THE 100 YEAR FLOOD LEVEL.
  - 3.2. PVB BACKFLOW DEVICES SHALL BE INSTALLED A MINIMUM OF 12" ABOVE THE HIGHEST DOWNSTREAM OUTLET.
  - 3.3. SEE DETAIL TOHO-02.1 TYPICAL BACKFLOW ASSEMBLY FOR ADDITIONAL REQUIREMENTS.
- 4. TOHO PROVIDES APPROVED IN-GROUND BACKFLOW DEVICES FOR 3/4" AND 1" POTABLE METERS COVERED BY THIS DETAIL.
- 5. CURB STOP SHALL BE INSTALLED WITH THE OPERATING NUT FACING UP.
- 6. NO PLANTINGS, STRUCTURES, OR OTHER UTILITIES, INCLUDING BUT NOT LIMITED TO TELECOM PEDESTALS, ELECTRICAL TRANSFORMERS OR POLES, ETC. SHALL BE INSTALLED WITHIN 36" OF ANY SIDE OF THE METER BOX.
- 7. BUILDER SHALL MAKE FINAL HORIZONTAL AND VERTICAL ADJUSTMENTS TO METER ASSEMBLY AND BOX:
  - 7.1. METER SHALL BE APPROXIMATELY 7" BELOW FINISHED GRADE AND CENTERED IN THE BOX.
  - 7.2. SINGLE LOT SERVICES SHALL HAVE BOX(ES) PERPENDICULAR TO THE CURB OR SIDEWALK.
  - 7.3. DOUBLE LOT SERVICES SHALL HAVE BOX(ES) PARALLEL TO THE CURB OR SIDEWALK.
  - 7.4. TOP OF METER BOX SHALL BE FLUSH WITH FINISH GRADE.
- 8. METER BOX LID SHALL BE BLACK SOLID PLASTIC WITH NO METAL ACCESS DOOR.



EFFECTIVE DATE:	04/01/2025
BOARD APPROVED DATE:	01/22/2025
PREVIOUS VERSION:	2022
DRAWN BY:	MP
REVISED BY:	DT

**TYPICAL POTABLE AND IRRIGATION SERVICE FOR COMMUNITIES WITHOUT REUSE WATER**

DRAWING NUMBER  
**01.1**